


Product Specifications

FlashCheck Lollipop Min/Max Thermometer

Measurement Range	-40°F to 311°F (-40°C to 155°C)
Operating Range	32°F to 122°F (0°C to 50°C)
Accuracy	±2°F (-40°F to -4°F); ±1°C (-40°C to -20°C) ±1°F(-4°F to 131°F); ±0.5°C (-20°C to 55°C) ±2°F (131°F to 311°F); ±1°C (55°C to 155°C) or ±1%, whichever is greatest
Sensor	Thermistor
Display Resolution	0.1°F /°C
Display Reading Update	1 second
Display Window Size	0.77 in W x 0.37 in H (19.5 mm W x 9.5 mm H)
Calibration	Factory calibrated to NIST traceable standards
Battery	Button Cell Alkaline
Body Casing	ABS plastic
Probe Dimensions	4.13" L x 0.14" Dia, Reduced tip 0.1" Dia (105 mm L x 3.56 mm Dia, Reduced tip 2.5 mm Dia)
Weight	1.25 oz. (35.4 gm)
Waterproof Rating	IP65
Certification	CE, RoHS, NIST traceable, manufacturers certificate of compliance available



Model 11040

- °F/°C selectable
- Min/Max memory stores lowest/highest readings
- Automatic calibration feature
- IP65 Waterproof
- Reduced Tip Probe
- Complies with FDA Food Code 4-203.11

DeltaTrak manufactures products under an ISO 9001:2008 registered quality management system

SS0183 15G1

