


Product Specifications

FlashCheck Jumbo Display Auto-Cal Digital Probe Lab Thermometer

Measurement Range	-40°F to 311°F (-40°C to 155°C)
Operating Range	32°F to 122°F (0°C to 50°C)
Accuracy	±1°F (14°F to 194°F), ±0.5°C (-10°C to 90°C) or ±1% whichever is greatest
Response Time	Less than 6 seconds between 32°F to 77°F (0°C to 25°C)
Sensor	Thermistor
Display Resolution	0.1°F/°C
Display Reading Update	Every 2 seconds
Display Window Size	1.5 in W x 0.5 in H (38mm W x 12.7mm H)
Calibration	Automatic Calibration button
Battery	Button cell alkaline
Body Casing	ABS Plastic
Probe Length	3.9 in (99mm)
Probe Diameter	0.14 in (3.56mm), reduced blunt tip 0.1 in (2.5mm)
Waterproof Rating	IP56
Factory Calibration	NIST traceable calibration
Compliance Certificate	Manufacturer's Certificate of Compliance, NIST traceable, CE Mark



Model 11062

- °F/°C selectable
- Automatic calibration
- Blunt, rounded tip ideal for scientific, laboratory and veterinary use
- Reduced tip probe provides less than 6 second response time
- Highly visible dual scale jumbo LCD display
- Sealed unibody construction
- IP56 waterproof, sanitizable, dirt and grease resistant
- Automatic shut off saves battery

DeltaTrak manufactures products under an ISO 9001:2008 registered quality management system

Patent No.
5,709,476
5,801,968



SS 11062 18B1

