

# FlashLink<sup>®</sup> mini

transport data recorder

## Product Specifications

operating range	-40° F to 150° F (-40° C to 66° C)
temperature accuracy	±1.0° F (0.5° C) From 32° F to 150° F (0° C to 66° C) ±2.0° F (1.0° C) over entire range
temperature resolution	0.1° F/° C
data capacity	3823 data points
Data download time	5 seconds
Manufacturer programmable alarm levels	High and low level throughout the temperature range
LED indicator	Flashing red alarm, green for operation
type of battery	Lithium battery 3v
size/enclosure	3.44" L x 2.07" W x 0.57" H; (87.38mm L x 52.72mm wide x 14.65mm high; ) ABS plastic housing
weight	1 oz. (28g)
authentication	CE Mark, NIST Traceability, RoHS Compliance
software requirements	Disposable FlashLink CT package #20178, or 20163 FlashPDF software package (both include CT-USB adapter) and Adobe Reader 7.0 or above



Models with Shipping Envelope	Models with Utility Sleeve
<b>Model 30013</b> 5-day (1 min. 54 sec. logging interval)	<b>Model 30013S</b> 5-day (1 min. 54 sec. logging interval)
<b>Model 30014</b> 15-day (5 min. 40 sec. logging interval)	<b>Model 30014S</b> 15-day (5 min. 40 sec. logging interval)
<b>Model 30015</b> 45-day (16 min. 58 sec. logging interval)	<b>Model 30015S</b> 45-day (16 min. 58 sec. logging interval)
<b>Model 30016</b> 75-day (28 min. 16 sec. logging interval)	<b>Model 30016S</b> 75-day (28 min. 16 sec. logging interval)

- Ideal for documenting storage and transport temperature conditions for temperature-sensitive products.
- Mini compact, single-use data logger
- Print data, download to PC using CT graphics printer or CT-USB adapter
- Unique shadow recording function ensures data recording even when the recorder is not activated

DeltaTRAK manufactures products under ISO9000 quality management

SS0120 13H1C



T:+86 755 8420 0058 | F:+86 755 2571 2314 | E:sales@eofirm.com | www.eofirm.com