

Product Specifications

FlashLink PDF

Multi-use data loggers

measuring range	-40° C to 50° C
temperature resolution	0.1° C
degree of accuracy	±0.5° C From -20° C to 45° C ±1.0° C above 45° C ±1.0° C below -20° C
data capacity	16112 points
Data download time	Usually 30 seconds.
Factory programmed alarms and delays	High/low limits over the entire temperature range
cell	Button battery lithium battery
size	49mm x 92mm x 17mm
shell	ABS plastic
weight	45.36 grams
shock resistance	Can withstand a 1 m drop to a hard surface
certificate	CE mark, traceable calibration NIST, RoHS compliant, BSS7061
show	LCD, LED red alarm
storage condition	-20° C to 50° C, 0% to 95% RH non-condensing
PDF standard	ISO19005-1, PDF/A, 21 CFR Part 11, ADOBE READER
minimum system requirements	PC and Windows Current operating systems
download request	Direct connection via USB



mode	99 time sin 7 days	60 time son the 15th	Availa ble 24 time son the 31st
°C	40200	40211	40220
°F	40201	40210	40221

- can be used multiple times
- No software required, or no programming recorder with PC
- No software required to download data
- USB port, no need for special reading equipment
- Stop recording after downloading data
- Automatically create secure PDF reports, CSV files
- Push button reset and restart recorder next time use
- Temperature history visible on LCD
- Manufacturers can provide customer-defined functions such as configuration record parameters,

alarm, delay start, etc.

Patent No. 6088514
<i>DeltaTRAK in ISO9001:2008 Production of products under quality management system</i>

SS0180_15D2



Shenzhen DTI Investment Development Co., Ltd. China Shenzhen City Longgang District Nanao Town Shuitousha Village Dongsha Road
No. 6 Sales: 86(755)8442-9007/8442-9388
Technical Support: 86(755)8442-9800 ext. 805 Fax: 86(755)84429388
www.deltatrakchina.com.cn, www.deltatrak.com