

Product Specifications Guaranteed recording stops at the end of transport

temperature range	Standard range: -29 ° C-38° C; High temperature range: 0° C -65° C; Low temperature range: -40° C -27° C
accuracy	±1° Cor better
inductor	bimetal coil
chart	Pressure sensitive, overall length 91.4mm ° F/°C dual temperature
driver	solid state quartz motor
Timing accuracy/ clock motor	Average ±20 seconds per month
cell	AA alkali-high temperature model; AA carbon-zinc-standard model; AA lithium-low temperature model
expiration date	3 years
size	13.5cm (L) x 10cm (W) x 6.3cm (H)



Models	5-Day	10-Day	20-Day	30-Day	60-Day	90-Day
standard range	16000	16100	16200	16300	16400	16500
high temperature range	16002	16102	16202	16302	16402	16502
low temperature range	16004	16104	16203		16403	
standard range ROHS Compliant	16000-1	16100-1	16200-1	16300-1	16400-1	16500-1
standard range ROHS Compliant	16002-1	16102-1	16202-1	16302-1	16402-1	16502-1
low temperature range ROHS Compliant	16004-1	16104-1	16203-1	16403-1		



Shenzhen Yiou
Technology Co., Ltd. Sales: 86 (755) 8420 0058 Fax:
86 (755) 2581 2314

E-mail: sales@szeo.cn
www.szeo.cn www.eofirm.com