

FlashLink® USB Logger

USBTransport Tank Recorder



DeltaTRAK's USB Transport Tank Recorder is ideal for monitoring and recording the temperature of viscous liquids during tank transport.

- Disposable 15-day trip recorder
- Simple and easy-to-read large screen LCD display
- The screen displays trip statistics
- Stainless steel probe cables made of food grade materials
- Weighted probe design to avoid floating in slurry
- IP54 Waterproof Recorder
- Patented Shadow Log feature guarantees valid data even in case of failed start operations

properties	specifications
Probe Test Range	-40°C to 65°C
temperature resolution	0.1°C
precision	±0.5°C from -10°C to 25°C; ±1.0°C above 25°C; Below ±1.0°C -10°C
data capacity	3823 points
Data download time	2 seconds download 3823 points
probe assembly	Stainless steel blunt tip, thermistor sensor and weighted immersible liquid; probe size: 1.6cm, weight: 0.40oz; overall cable length 2.5 m; from The cable length calculated by red mark is 1.5m
Programmable alarm level	High and low levels throughout the range
cell	(CR2032) 3.6V lithium / 18 months
size/enclosure	1.575" x 3.189" x 0.575" (40mm x 81mm x 13mm)
housing	PC/ABS plastic
authentication	CE certified, factory calibrated to NIST standards, RoHS compliant
display	LCD display, red LED alarm
waterproof level	IP54 waterproof
storage condition	-20°C to 50°C 0% to 95%RH
minimum system requirements	Windows PC and XP, or higher
Programming and downloading	USB interface directly connected to PC, FlashPDF program manager software (serial number PN20412) or USB program manager software (PN 20238), and Adobe Reader 7.0 or later

Shenzhen EO Technology Co., Ltd Ltd.

Address: Room 909, No. 13, Hehun Lane 1, Wuhe Avenue, Bantian, Longgang District, Shenzhen

Add: Rm 909, No. 13 1st Lane Hekan, Wuhe Avenue BanTian , LongGang Area, ShenZhen

Tel: (86 755) 8420 0058 Fax: (86 755) 2822 5583 E-mail: sales@szeo.cn <http://www.szeo.cn>