

# 使用说明



## 使用说明

1. 确保在使用前用热水清洗金属探针并对其进行消毒。
2. 使用温度计正面的“开/关”按钮开机。该温度计具有自动关闭功能，在10分钟内无操作将自动进入省电模式，以节省电池寿命。
3. 温度计正面标有“C/F”的按钮选择华氏度或摄氏度。
4. 当进行测试时，将探头插入食物至少1CM，确保尖端不接触骨头或脂肪。大约6秒后，显示当前温度。
5. 当数字显示稳定后，按下“HOLD”按钮，温度将保持在显示屏上（显示字母“H”）。再次按下“HOLD”按钮以释放此功能。
6. 该温度计具有最高和最低温度记忆功能。按下温度计表面的MAX（最高），您将看到最高记录温度。按第二次，您将看到记录的MIN温度。再次按下以清除该单元。
7. 为避免烫伤，装置的盖子将锁定在延长温度计长度的手柄上。
8. 使用后，清洁探头并消毒。
9. 该温度计防水，可在水中浸泡15分钟；但它不可以放在洗碗机里。

## 校准

温度计具有独特的校准功能，可以在任何温度下校准。要校准设备，请按下设备表面的“CAL”校准键，LCD显示屏上会出现“CALL”。

将探头放入已知温度的水中（冰水或沸水）。要增加温度，请按“C/F”键，温度将以度为单位增加。

要降低温度，请按下“HOLD”按钮。校准温度后，按下“CAL”校准按钮完成校准。

brand	TempTrak
Model	E310
type	reuse
Temperature range	-50°C~300°C
precision	±0.5°C(-10°C to 100°C), other±1.5°C
sensor	Thermistor
temperature resolution	0.1°C
Show read updates	1second
reaction rate	Less than 4 seconds
Display window size	30 mm Width x 13 mm height
calibration	Automatic calibration function
Battery	A76Alkaline button battery
Body Housing/Probe	Polycarbonate and ABS plastics/stainless steel
Probe length	70 mm
probe diameter	3.5 mm, probe tip 1.7mm
Add pipe sleeve length	250mm
weight	22g
Waterproof grade	IP67