



The **easiest and most economical** option for cold chain monitoring!



TrekTag Features



Encrypted PDF data reports
Automatically generate encrypted PDF data reports without any software.



Integrated USB interface
Quickly connect to a computer anytime, anywhere to access data without any cables or readers.



EN12830

Compliance with EN12830
Comply with EN12830:1999 Directive (for transport, storage and distribution of refrigerated, frozen, deep-frozen and frozen food or other goods)



Factory parameter preset
The required parameters are preset by the factory, and only need to press the key to start before use!



IP67 protection class
Food grade composite bag, completely waterproof, meets IP67 protection level.



Comply with Air Transport Safety Directive
It conforms to RTCA/DO-160 airborne equipment environmental conditions and test procedures, and is suitable for air transportation of equipment in activated state.

| | |
|-----------------------------------|---|
| brand | TrekTag |
| Model | P30 |
| type | single use |
| sensor | Built-in high-precision NTC sensor |
| data capacity | 14400 group |
| Temperature measurement range | -30°C to 70°C (-22°F to 158°F) |
| temperature measurement accuracy | ±0.3°C/±0.9°F(-10C~70C), Other ranges±1°C/±1.8°F |
| resolution | 0.1°C /°F |
| startup mode | Manual start/delayed start (factory configuration) |
| recording interval | 1 minute to 2 hours optional |
| Battery | 3.0v lithium battery |
| startup mode | Manual start/delayed start (factory configuration) |
| recording interval | 1 minute to 2 hours optional |
| Alarm mode | High and low temperature alarm (factory configuration) |
| Alarm type | Single type/cumulative type |
| recording period | 24 Hours to 120 days optional |
| typical running time | 120God |
| shelf life | 2year |
| display | LEDindicator light •Normal, Alarm, Running status |
| key | Start/stop |
| interface | USB 2.0 |
| data type | •Temperature • Date/Time |
| Automatically generate data files | Encrypted PDF data reports/Excel forms |
| Operating system compatibility | WIN XP/7/8/10 |
| certification | CE, FCC, EN12830,UN38.3,Certificate of Appraisal of Conditions of Carriage of Air Cargo |
| size | WIN XP/7/8/10 |
| weight | about15g |
| Packaging/Materials | Food grade composite bag/nylon+PE |
| Protection class | IP67 |