

Cooper-Atkins™ Multi-Function Thermometer Kit 92020

The 92020 Kit is made up of the MFT 20200 instrument and the 51337-K DuraNeedle Direct Connect Flanged Probe with screw-in flanged connector. The MFT instrument transmits temperatures wirelessly to your mobile device via Bluetooth Low Energy. It can utilize any Cooper-Atkins' type-K thermocouple temperature probe, making it versatile for insertion, air or surface temperature measurement.

Kit includes:

- 20200 MFT instrument
- 51337-K DuraNeedle Direct Connect Probe with screw-in flanged connection



| 20200 Specifications |
|---|
| Temperature Range: -100° to 1000°F (-73° to 538°C) |
| Accuracy: +/- 0.5°F (+/- 0.3°C) at ambient between 68° to 86°F (20° to 30°C). Add +/- 0.1° to accuracy spec per 1° change to ambient temperature outside of 68° to 86°F |
| Ambient Operating Range: -4° to 122°F (-20° to 50°C). 10% to 90% RH, non-condensing |
| Resolution: 0.1°F/0.1°C |
| Radio Protocol: Bluetooth Low Energy 2.4 GHz |
| RF Range: 100 ft open-field range |
| Power: (1) AA Alkaline battery |
| Battery Life: 500 hours |
| 5-year Warranty |
| IPX7 waterproof rated |

51337-K DuraNeedle Probe with Flanged Connector

- Temperature Range: -100° to 500°F (-73° to 260°C)
- Accuracy: +/- 1°F (+/- 0.5°C)
- Response Time: 1 second in liquid
- Probe Length: 4" (102 mm)
- 1-year warranty



Note: EMC Compliance: The instrument may record temperature measurements beyond the stated accuracy when exposed to radio frequency disturbances between 250Mhz and 1000Mhz with a field strength in excess of 3.0V/m. This deviation is temporary and the device will recover when the disturbance is removed.

