

product standard

FlashCheck Min/Max Digital Alarm Thermometer

measuring range	-50°C to 70°C (-58°F to 158°F)
working range	-10°C to 50°C (14°F to 122°F)
accuracy	±0.5°C (-30°C to 55°C) ±1.0°F (-22°F to 131°F); otherwise ±1.0°C (±1.8°F)
display resolution	0.1°F/°C
Show reading updates	17seconds
Display size	49 mm wide x 53 mm long
Instrument size	W 2.99 x L 3.74 x D 0.74 (width 76 mm x length 95 mm x depth 19mm)
instrument housing	ABSPolymer, chemical resistance, high impact
sensor	thermistor
External probe type/size	Stainless steel, 17.8 mm long x 5 mm diameter
line of induction	3 m x 2mm diameter
cell	AAbattery, user replaceable
Certification/Calibration	CE Mark, NIST Traceability, RoHS, WEEE



Model 12217

- Min/Max memory for minimum and maximum readings
- High and low alarms with buzzer and flashing red light
- Removable external sensor with gold-plated stereo jack connector
- Large LCD screen
- Optional °C/°F temperature scale
- Blunt probe sensor with 3 m cable
- residual battery indicator
- nonvolatile memory retains settings during battery replacement
- Use rugged built-in magnets to mount to vertical surfaces
- Foldable stand that can be placed on a flat surface

DeltaTrak manufactures products according to ISO 9001:2015 Registered

SS 12217 CH 20D1

