

# Product Specifications

## FlashLink Mini PDF In-Transit Logger

<b>Measurement Range</b>	-40°F to 188.6°F (-40°C TO 87°C)
<b>Accuracy</b>	±1.0°F from -4°F to 14°F (±0.5°C from -20°C to -10°C) ±0.6°F from 14°F to 50°F (±0.4°C from -10°C to 5°C) ±1.0°F from 50°F to 77°F (±0.5°C from 5°C to 25°C) ±1.8°F if < -4°F or > 77°F (±1.0°C if < -20°C or > 25°C)
<b>Data Download Time</b>	30 seconds typical
<b>Factory Programmable Alarms</b>	High & Low levels over entire range
<b>Delay Start</b>	30 minutes
<b>Battery</b>	Coin Cell Battery
<b>Dimensions</b>	1.858in x 3.071in x 0.402in (47.2mm x 78mm x 10.2mm)
<b>Weight</b>	0.854 oz. (24.2 grams)
<b>Shelf Life</b>	18 Months
<b>Certification</b>	CE Mark, Calibration traceable to NIST, RoHS Compliant
<b>Display</b>	Green and Red LED
<b>Waterproof Rating</b>	IP54 with silicone cap
<b>Storage Conditions</b>	-4°F to 122°F (-20°C to 50°C) 0% to 95% RH w/o condensation
<b>System Requirements</b>	Windows PC with current operating system Adobe Reader
<b>Download Requirements</b>	Direct USB connection to PC, tablet or printer



FlashLink Mini PDF with high visibility locator card

Model	31010	31011	31012
<b>Low/High Alarm Settings</b>	None	2°C/8°C	15°C/25°C
<b>Sample Rate</b>	10 Min	5 Min	5 Min
<b>Data Capacity</b>	12,288 data points	12,288 data points	12,288 data points
<b>Trip Duration</b>	85 Days	42.5 Days	42.5 Days
<b>Temperature Scale</b>	°F/°C	°F/°C	°F/°C

- Compact, single-use temperature logger
- Shadow Log® guarantees trip data
- No software required for download
- Built-in USB connector, no special reading device needed
- On-board software automatically creates PDF and CSV reports in °F and °C
- View reports on a PC or tablet
- Recorded data automatically scaled to graph
- GMT/UTC: 0

Patent No. 6,088, 514

DeltaTrak manufactures products under an ISO 9001:2015 registered quality management system

