

## FlashLink<sup>®</sup> USB PDF Reusable data logger

Measuring range	-40 to 50 °C
temperature resolution	0.1 °C
accuracy	± 0.5 From -10 °C to 25 ± 1.0 °C Above 25 1.0 °C Below -100
data capacity	32.496 data points
data download time	Usually about 3823 data points in 5 seconds
Programmable alarm level Programmable alarm level	The entire range of high and low levels is displayed on the LCD
Battery	Two AAA lithium batteries, the LCD indicates the remaining power%.
Size/Body	40 mm x 93 mm x 24 mm
weight	54.3 grams
shell	PC/ABS plastic
impact resistance	Can withstand a 1-meter drop to a hard surface
certification	CE marking, NIST traceability, RoHS compliant
FAA compliance	RTCA/D0-160
show	LCD.Red LED alarm
Waterproof grade	IP64 (when silicone cap is closed)
Storage conditions	-20 °C to 50 °C 0% to 95% RH non-condensing
System requirements	Windows PC with current operating system Adobe Reader
Programming	FlashPDF program manager software
download requirements	Direct USB connection



### 型号 40510

- Single channel, internal sensor
- Automatically generate reports and CSV files in PDF format
- Suitable for monitoring ambient temperature
- User programmable: manual or automatic start, recording interval high/low alarms
- Large, easy-to-read LCD display
- Multilingual FlashPDF program management software
- Data summary and analysis, and alarm information
- Degree minutes and MKT (mean kinetic temperature) calculations
- USB port, reusable

DeltaTrak 在 ISO9001:2008 质量管理体系下生产产品

SS 40510 16H1



---