


Product Specifications

FlashCheck Jumbo Display Auto-Cal Reduced Tip Probe Thermometer

Measurement Range	-40°F to 311°F (-40°C to 155°C)
Operating Range	32°F to 122°F (0°C to 50°C)
Accuracy	±1°F (14°F to 194°F), ±0.5°C (-10°C to 90°C) or ±1% whichever is greatest
Response Time	Less than 6 seconds between 32°F to 77°F (0°C to 25°C)
Sensor	Thermistor
Display Resolution	0.1°F/°C
Display Reading Update	Every 2 seconds
Display Window Size	1.5 in W x 0.5 in H (38mm W x 12.3mm H)
Battery	Button cell alkaline
Body Casing	ABS Plastic
Probe Length	3.9 in (99mm)
Probe Diameter	0.14 in (3.56 mm), 14 gauge needle tip 0.067 in (1.7mm)
Waterproof Rating	IP56
Factory Calibration	NIST traceable calibration
Compliance Certificate	Manufacturer's Certificate of Compliance, NIST traceable, CE, RoHS



Reduced Tip Probe



Probe Protection Cap

Model 11081

- Automatic calibration feature
- Reduced tip probe provides less than 6 second response time
- Sealed unibody construction
- IP56 waterproof and grease resistant
- Probe fits standard Pete's plug self-closing valve
- Automatic shut off saves battery
- High visibility dual scale jumbo LCD display
- °F/°C selectable

DeltaTrak manufactures and operates under an ISO 9001:2015 registered quality management system

Patent No. 5,709,476 5,801,968



SS 11081 21D1

