

# Product Specifications

## Jumbo Display Wall Mount Thermo-Hygrometer

<b>Temperature Range</b>	Internal: 14°F to 122°F (-10°C to 50°C) External Probe: -58°F to 158°F (-50°C to 70°C)
<b>Humidity Range</b>	Internal: 10% to 99%
<b>Temperature Accuracy(Int. &amp; Ext.)</b>	±1.8°F (1°C) from 32°F to 104°F (0°C to 40°C)
<b>Humidity Accuracy(Internal)</b>	±5% R.H. from 40% to 70% R.H. at 77°F~86°F (25°C~30°C)
<b>External Temperature Sensor</b>	Cable length: 6.56 ft / 2 meters; Probe: 20mm L x 4mm Diameter
<b>Resolution</b>	R.H.1%, temperature 0.1°F /°C
<b>Display Window Size</b>	3.15in. W x 2.36in. H (80mm W x 60mm H)
<b>Character Height within Display</b>	1.02in (26mm) - Temperature & Humidity 0.87in (22mm) - Date & Time
<b>Product Size</b>	3.74in. W x 4.02in. H x 0.75 in. D (95mm W x 102mm H x 19mm D)
<b>Weight</b>	4.18 oz. (118.4 g)
<b>Body Casing</b>	Polycarbonate and ABS plastic
<b>Sensor Type</b>	Temperature: thermistor Humidity: electronic resistive
<b>Battery</b>	AAA (quantity 1 each)
<b>Certification/ Calibration</b>	CE mark, NIST traceable calibration certificate



### Model 13309

- Internal temperature and humidity sensors
- External temperature probe
- Probe holder with self-adhesive backing
- °C/°F selectable
- Jumbo display for temperature, humidity, time and date
- Min/Max memory - lowest and highest readings stored for instant recall
- Daily alarm and hourly chime

DeltaTrak manufactures products under an ISO 9001:2015 registered quality management system

SS 13309 20E1

