

# Product Specifications

## FlashCheck. Waterproof Min/Max Folding Probe Thermometer

<b>Measurement Range</b>	-58°F to 572°F (-50°C to 300°C)
<b>Operating Range</b>	32°F to 122°F (0°C to 50°C)
<b>Accuracy</b>	±1.8°F from -58°F to +23°F (±1.0°C from -50°C to -5°C), ±0.5°F from +28°F to +149°F (±0.5°C from -5°C to +65°C), ±1.8°F from 149°F to +572°F (±1.0°C from 65°C to 300°C)
<b>Response Time</b>	Under 4 seconds
<b>Sensor</b>	Thermistor
<b>Display Resolution</b>	0.2°F / 0.1°C
<b>Display Reading Update</b>	Every 0.25 seconds
<b>Display Window Size</b>	1.68 in W x 0.65 in H (42.7mm W x 16.6mm H)
<b>Calibration</b>	Automatic Calibration button
<b>Battery</b>	CR2032 3V Li coin cell battery
<b>Auto Shut-Off</b>	10 minutes
<b>Body Casing</b>	ABS Plastic
<b>Probe Length</b>	4.7in (120mm)
<b>Probe Diameter</b>	Food grade safety 304 stainless steel probe 0.067in (1.7mm)
<b>Waterproof Rating</b>	IP67
<b>Factory Calibration</b>	NIST traceable calibration



### Model 15051

- Instant temperature reading
- Foldable probe for safe handling
- Magnetic back surface
- Hold feature locks temperature reading
- Ideal for thin mass foods such as meat patties, chicken and fish fillets
- Min/Max memory stores lowest/highest readings
- °F/°C selectable
- Measures up to 572°F (300°C)
- Backlit display
- Automatic calibration feature
- Highly visible dual scale jumbo LCD display
- IP67 waterproof, sanitizable, dirt and grease resistant
- Powers on automatically when unfolding probe
- Automatic shut off saves battery life
- Complies with FDA Food Code 4-203.11

DeltaTrak manufactures products under an ISO 9001:2015 registered quality management system

SS 15051 22C1

