


# Product Specifications

## FlashLink USB PDF Reusable Data Logger

<b>Measurement Range</b>	-40°F to 116°F (-40°C to 47°C)
<b>Temperature Resolution</b>	0.1°C over full temperature measurement range
<b>Accuracy</b>	±0.5°C from 0°C to 25°C ±1.0°C from 25°C to 47°C ±1.0°C from -40°C to 0°C
<b>Data Capacity</b>	16,000 data points
<b>Data Download Time</b>	5 seconds typical for 3823 points
<b>Factory Programmable Alarm Levels</b>	High & Low levels over entire range, displayed on LCD
<b>Battery</b>	2 x AAA Lithium batteries, user replaceable Option to replace with 2 X AAA alkaline batteries
<b>Dimensions</b>	1.57" x 3.67" x 0.94" (40mm x 93.5 mm x 24mm)
<b>Casing</b>	PC/ABS plastic
<b>Weight</b>	1.9 oz. (54 grams)
<b>Shock Resistance</b>	Withstands 3-foot (1 meter) drop to hard surface
<b>Certification</b>	CE Mark, NIST traceable, ROHS Compliant, BSS 7061 Compliant
<b>FAA Compliance</b>	RTCA/DO-160
<b>Display</b>	Red LED Alarm
<b>IP Rating</b>	IP54 (with silicon cap on)
<b>Storage conditions</b>	-4°F to 122°F (-20°C to 50°C) 0% to 95% RH w/o condensation
<b>System Requirements</b>	Windows PC with current operating system Adobe reader
<b>Programming</b>	FlashLink Program Manager Software
<b>Download Requirements</b>	Direct USB connection



### Model 40516

- Single channel, internal sensor
- Automatically generates PDF report and CSV file
- Ideal for monitoring ambient temperature
- User programmable: manual or auto start, logging intervals, high/low alarms
- Large easy-to-read LCD
- Multi-language FlashLink Program Manager software
- Summary analysis of data, with alarm information
- Degree Minutes and MKT calculations

Patent No. 6,088,514

DeltaTrak manufactures products under an ISO 9001:2015 registered quality management system

SS\_40516\_21B2

