

Product Specifications

FlashCheck Jumbo Display Auto-Cal Blunt Probe Thermometer

Measurement Range	-40°F to 311°F (-40°C to 155°C)
Operating Range	32°F to 122°F (0°C to 50°C)
Accuracy	±1.8°F from -40°F to -5°F (±1°C from -40°C to -21°C), ±0.9°F from -4°F to 104°F (±0.5°C from -20°C to 40°C), ±1.8°F from 105°F to 311°F (±1°C from 41°C to 155°C)
Response Time	Less than 6 seconds between 32°F to 77°F (0°C to 25°C)
Sensor	Thermistor
Display Resolution	0.1°F/°C
Display Reading Update	Every 2 seconds
Display Window Size	1.5in W x 0.5in H (38mm W x 12.7mm H)
Battery	Button cell alkaline
Body Casing	ABS plastic
Probe Length	4.1in (104mm)
Probe Diameter	0.137in (3.50mm), reduced blunt tip 0.1in (2.60mm)
Waterproof Rating	IP56
Factory Calibration	NIST traceable calibration
Compliance Certificate	Manufacturer's Certificate of Compliance, NIST traceable, NSF, CE



Model 11082

- Automatic calibration feature
- Blunt, rounded tip ideal for scientific, laboratory and veterinary use
- Reduced tip probe provides less than 6 second response time
- Highly visible dual scale jumbo LCD display
- IP56 waterproof, sanitizable, dirt and grease resistant
- Automatic shut off saves battery
- NSF certified
- °F/°C selectable

DeltaTrak manufactures and operates under an ISO 9001:2015 registered quality management system



SS 11082 21E1

