

Product Specifications

FlashLink Mini PDF In-Transit Logger

Measurement Range	-40°F to 140°F (-40°C TO 60°C)
Accuracy	±1.0°F from -4°F to 14°F (±0.5°C from -20°C to -10°C) ±0.6°F from 14°F to 50°F (±0.3°C from -10°C to 10°C) ±1.0°F from 50°F to 77°F (±0.5°C from 10°C to 25°C) ±1.8°F if < -4°F or > 77°F (±1.0°C if < -20°C or > 25°C)
Data Download Time	5 seconds typical
Factory Programmable Alarms	High & Low levels over entire range
Delay Start	30 minutes
Battery	Coin Cell Battery
Dimensions	1.858in x 3.071in x 0.402in (47.2mm x 78mm x 10.2mm)
Weight	0.854 oz. (24.2 grams)
Shelf Life	18 Months
Certification	RTCA/DO-160G Sect 21.5, CE Mark, Calibration traceable to NIST, RoHS Compliant
Display	Green and Red LED
Waterproof Rating	IP54 with silicone cap
Storage Conditions	-4°F to 122°F (-20°C to 50°C) 0% to 95% RH w/o condensation
System Requirements	Windows PC with current operating system Adobe Reader
Download Requirements	Direct USB connection to PC, tablet or printer



FlashLink Mini PDF with high visibility locator card

Model	31010	31011	31012
Low/High Alarm Settings	None	2°C/8°C	15°C/25°C
Sample Rate	10 Min	5 Min	5 Min
Data Capacity	12,288 data points	12,288 data points	12,288 data points
Trip Duration	85 Days	42.5 Days	42.5 Days
Temperature Scale	°F/°C	°F/°C	°F/°C

- Compact, single-use temperature logger
- Shadow Log® guarantees trip data
- No software required for download
- Built-in USB connector, no special reading device needed
- On-board software automatically creates PDF and CSV reports in °F and °C
- View reports on a PC or tablet
- Recorded data automatically scaled to graph
- GMT/UTC: 0

Patent No. 6,088, 514

DeltaTrak manufactures products under an ISO 9001:2015 registered quality management system

SS 31010-X 21B1

